



苏州莱能士光电科技有限公司
SuZhou LightIns Optical Technology Co.,LTD

技术规格书 (Specifications)

型号 (Name)		128FH2024B	规格 (Key Parameter)		f2.0mm 1/2.8" F2.4		
No.	名称 (Item Name)	参数 (Parameter)	No.	名称 (Item Name)	参数 (Parameter)		
1	传感器 (Sensor)	CCD/CMOS	11	机械后焦 (BackFocalLength)	2.93mm		
2	像面规格 (Image Size)	1/2.8"	12	系统总长 (TTL)	14.47±0.2mm		
3	焦距 (Focal Length)	2.0±5%mm	13	畸变率 (%) (Distortion)	-112%		
4	光圈范围 (Aperture)	2.4±5%	14	工作温度 (Operating Temperature)	-40° - +105°C		
5	分辨率 (Resolution)	3Mega Pixel	15	接口 (Mount)	M12×P0.5-6g		
6	主光线角度 (Chief Ray Angle)	18°	16	外形尺寸 (Dimension)	φ16×11.54		
7	日夜共焦 (IR Corretion)	Yes	17	镜头组成 (Lens Construction)	6Glass		
8	视场角 (F.O.V) Vs 像高 (D×H×V)	SC1235	180°×138°×100°	18	操作方法 (Operation)	焦点 (Focal)	手动 (Manual)
9		IMX290	205°×169.5°×90° (6.47×5.64×3.18)	19		焦距 (Zoom)	固定 (Fixed)
10		IMX323	198°×151°×88° (6.36×5.558×3.094)	20		光圈 (Iris)	固定 (Fixed)

